



ESSENCE LINE



SPECIFICATON DESCRIPTION CUBICLE TYPE "ESSENCE" ON FEET H2042

- 44.42 PRE-ASSEMBLED WALL SYSTEMS
- 44.42.40- a. PANEL SYSTEM WALL, PRE-ASSEMBLED WALL SYSTEMS, SOLID GRADE LAMINATE (SGL)
0. PANEL SYSTEM WALL
1. SANITARY CUBICLE PARTITIONS
- Manufacture : KUPAN B.V. Varsseveld The Netherlands
- Type : Essence on feet H2042
- Construction element:**
- Solid Grade Laminate melamine resin sheets (SGL) 13 mm
 - walls are attached internally and upon structural walls by means of natural anodised aluminium continuous U profiles
 - pilasters/end walls are provided with natural anodised aluminium door stop sections with PVC damper for soundproofing
 - places upon aluminium adjustable feet (screwed or glued together on the floor)
 - finish: SGL
- Standard dimensions wall elements** (differences are possible, with the exception of the thickness)
- | | | |
|--|---------|---------------------------|
| - thickness side/partition walls and pilasters (front) | 13 mm | |
| - cubicle height | 2042 mm | |
| - passage height | 1995 mm | |
| - clear space between bottom of the finished floor and walls | 180 mm | |
| - height partition and splash walls | 1820 mm | (infant cubicles 1200 mm) |
| - height front and side walls | 1820 mm | |
| - width and depth of the sanitary cubicle depends on project and/or according to drawing | | |
- Doors**
- self-closing
- Standard dimensions doors** (differences are possible, with the exception of the thickness)
- | | | |
|------------------|---------------|---------------------------|
| - thickness | 13 mm | |
| - height | 1820 mm | (infant cubicles 1200 mm) |
| - width | 615 to 750 mm | (MIVA 915 mm) |
| - entrance width | 600 to 735 mm | (MIVA 900 mm) |
- Hinges and locks**
- Finger safe aluminium translating hinges. Self closing by translation movement, 180 ° degrees opening, including anti-theft device
 - Kupan free and occupied lock with integrated handgrip, natural anodised aluminium, with red-white indication and brass emergency pin, allows opening from the outside in case of an emergency
- Supporting structure**
- on feet, 180 mm high natural anodised aluminium foot with ABS plastic rosette.
- Fittings and Accessories**
- bench and splash wall for showers
 - bench with central locking system for changing cubicles
 - coat hooks, natural anodised aluminium
 - modesty partitions for urinals, 13 mm SGL sheet with aluminium anodised wall clamps
 - soap and shampoo plateaus (planchets)
 - toilet roll holder
 - washstand sheets and washbasins
 - rim/safety locks
 - soap dishes
 - mirrors
 - SGL lockers
 - pictograms
 - lighting galleries
 - aluminium profiles in RAL colour
5. **DRAWINGS**
- By manufacturer made drawings. Also in 3D and BIM
- Working drawing(s) based on supplied principle arrangement drawing(s) by the management
- Amount of supplied copies:
- for approval: PDF format by e-mail
- Definite : PDF format by e-mail
6. **PROCESSING INSTRUCTIONS MANUFACTURER**
- Assembly and mounting**
- pre assembled in factory
- Installation**
- supplied processing regulations in accordance with the manufacturer.
 - if required by KUPAN BV
- Warranty**
- 1 year on hinges and locks
 - 5 years on SGL Sheet/Panels
01. **INDOOR SEPARATION**
- The partition walls in the sanitary spaces as indicated on finished condition and drawings.



ESSENCE LINE



SPECIFICATON DESCRIPTION CUBICLE TYPE "ESSENCE" ON FEET H2262

- 44.42 PRE-ASSEMBLED WALL SYSTEMS
- 44.42.40- a. PANEL SYSTEM WALL, PRE-ASSEMBLED WALL SYSTEMS, SOLID GRADE LAMINATE (SGL)
0. PANEL SYSTEM WALL
1. SANITARY CUBICLE PARTITIONS
- Manufacture : KUPAN B.V. Varsseveld The Netherlands
- Type : Essence on feet H2262
- Construction element:**
- Solid Grade Laminate melamine resin sheets (SGL) 13 mm
 - walls are attached internally and upon structural walls by means of natural anodised aluminium continuous U profiles
 - pilasters/end walls are provided with natural anodised aluminium door stop sections with PVC damper for soundproofing
 - places upon aluminium adjustable feet (screwed or glued together on the floor)
 - finish: SGL
- Standard dimensions wall elements** (differences are possible, with the exception of the thickness)
- | | | |
|--|---------|---------------------------|
| - thickness side/partition walls and pilasters (front) | 13 mm | |
| - cubicle height | 2262 mm | |
| - passage height | 2215 mm | |
| - clear space between bottom of the finished floor and walls | 180 mm | |
| - height partition and splash walls | 2040 mm | (infant cubicles 1200 mm) |
| - height front and side walls | 2040 mm | |
| - width and depth of the sanitary cubicle depends on project and/or according to drawing | | |
- Doors**
- self-closing
- Standard dimensions doors** (differences are possible, with the exception of the thickness)
- | | | |
|------------------|---------------|---------------------------|
| - thickness | 13 mm | |
| - height | 2040 mm | (infant cubicles 1200 mm) |
| - width | 615 to 750 mm | (MIVA 915 mm) |
| - entrance width | 600 to 735 mm | (MIVA 900 mm) |
- Hinges and locks**
- Finger safe aluminium translating hinges. Self closing by translation movement, 180 ° degrees opening, including anti-theft device
 - Kupan free and occupied lock with integrated handgrip, natural anodised aluminium, with red-white indication and brass emergency pin, allows opening from the outside in case of an emergency
- Supporting structure**
- on feet, 180 mm high natural anodised aluminium foot wit ABS plastic rosette.
- Fittings and Accessories**
- bench and splash wall for showers
 - bench with central locking system for changing cubicles
 - coat hooks, natural anodised aluminium
 - modesty partitions for urinals, 13 mm SGL sheet with aluminium anodised wall clamps
 - soap and shampoo plateaus (planchets)
 - toilet roll holder
 - washstand sheets and washbasins
 - rim/safety locks
 - soap dishes
 - mirrors
 - SGL lockers
 - pictograms
 - lighting galleries
 - aluminium profiles in RAL colour
5. **DRAWINGS**
- By manufacturer made drawings. Also in 3D and BIM
- Working drawing(s) based on supplied principle arrangement drawing(s) by the management
- Amount of supplied copies:
- For approval : PDF format by e-mail
- Definite : PDF format by e-mail
6. **PROCESSING INSTRUCTIONS MANUFACTURER**
- Assembly and mounting**
- pre assembled in factory
- Installation**
- supplied processing regulations in accordance with the manufacturer.
 - if required by KUPAN BV
- Warranty**
- 1 year on hinges and locks
 - 5 years on SGL Sheet/Panels
01. **INDOOR SEPARATION**
- The partition walls in the sanitary spaces as indicated on finished condition and drawings.



SPECIFICATON DESCRIPTION CUBICLE TYPE "ESSENCE" FREELY SUSPENDED H2042

- 44.42 PRE-ASSEMBLED WALL SYSTEMS
- 44.42.40- a. PANEL SYSTEM WALL, PRE-ASSEMBLED WALL SYSTEMS, SOLID GRADE LAMINATE (SGL)
0. PANEL SYSTEM WALL
1. SANITARY CUBICLE PARTITIONS
- Manufacture : KUPAN B.V. Varsseveld The Netherlands
Type : Essence Semi freely suspended H2042 (reduced feet system)
- Construction element:**
- Solid Grade Laminate melamine resin sheets (SGL) 13 mm
 - walls are attached internally and upon structural walls by means of natural anodised aluminium continuous U profiles
 - pilasters/end walls are provided with natural anodised aluminium door stop sections with PVC damper for soundproofing
 - places upon aluminium adjustable feet (screwed or glued together on the floor)
 - finish: SGL
- Standard dimensions wall elements** (differences are possible, with the exception of the thickness)
- | | | |
|--|---------|---------------------------|
| - thickness side/partition walls and pilasters (front) | 13 mm | |
| - cubicle height | 2042 mm | |
| - passage height | 1995 mm | |
| - clear space between bottom of the finished floor and walls | 180 mm | |
| - height partition and splash walls | 1820 mm | (infant cubicles 1200 mm) |
| - height front and side walls | 1820 mm | |
| - width and depth of the sanitary cubicle depends on project and/or according to drawing | | |
- Doors**
- self-closing
- Standard dimensions doors** (differences are possible, with the exception of the thickness)
- | | | |
|------------------|---------------|---------------------------|
| - thickness | 13 mm | |
| - height | 1820 mm | (infant cubicles 1200 mm) |
| - width | 615 to 750 mm | (MIVA 915 mm) |
| - entrance width | 600 to 735 mm | (MIVA 900 mm) |
- Hinges and locks**
- Finger safe aluminium translating hinges. Self closing by translation movement, 180 ° degrees opening, including anti-theft device
 - Kupan free and occupied lock with integrated handgrip, natural anodised aluminium, with red-white indication and brass emergency pin, allows opening from the outside in case of an emergency
- Supporting structure**
- on feet, 180 mm high natural anodised aluminium foot wit ABS plastic rosette.
- Fittings and Accessories**
- bench and splash wall for showers
 - bench with central locking system for changing cubicles
 - coat hooks, natural anodised aluminium
 - modesty partitions for urinals, 13 mm SGL sheet with aluminium anodised wall clamps
 - soap and shampoo plateaus (planchets)
 - toilet roll holder
 - washstand sheets and washbasins
 - rim/safety locks
 - soap dishes
 - mirrors
 - SGL lockers
 - pictograms
 - lighting galleries
 - aluminium profiles in RAL colour
5. **DRAWINGS**
- By manufacturer made drawings. Also in 3D and BIM
Working drawing(s) based on supplied principle arrangement drawing(s) by the management
Amount of supplied copies:
For approval : PDF format by e-mail
Definite : PDF format by e-mail
6. **PROCESSING INSTRUCTIONS MANUFACTURER**
- Assembly and mounting**
- pre assembled in factory
- Installation**
- supplied processing regulations in accordance with the manufacturer.
 - if required by KUPAN BV
- Warranty**
- 1 year on hinges and locks
 - 5 years on SGL Sheet/Panels
01. **INDOOR SEPARATION**
- The partition walls in the sanitary spaces as indicated on finished condition and drawings.



ESSENCE LINE



SPECIFICATON DESCRIPTION CUBICLE TYPE "ESSENCE" FREELY SUSPENDED H2262

- 44.42 PRE-ASSEMBLED WALL SYSTEMS
- 44.42.40- a. PANEL SYSTEM WALL, PRE-ASSEMBLED WALL SYSTEMS, SOLID GRADE LAMINATE (SGL)
0. PANEL SYSTEM WALL
1. SANITARY CUBICLE PARTITIONS
- Manufacture : KUPAN B.V. Varsseveld The Netherlands
- Type : Essence Semi freely suspended H2262 (reduced feet system)
- Construction element:**
- Solid Grade Laminate melamine resin sheets (SGL) 13 mm
 - walls are attached internally and upon structural walls by means of natural anodised aluminium continuous U profiles
 - pilasters/end walls are provided with natural anodised aluminium door stop sections with PVC damper for soundproofing
 - places upon aluminium adjustable feet (screwed or glued together on the floor)
 - finish: SGL
- Standard dimensions wall elements** (differences are possible, with the exception of the thickness)
- | | | |
|--|---------|---------------------------|
| - thickness side/partition walls and pilasters (front) | 13 mm | |
| - cubicle height | 2262 mm | |
| - passage height | 1995 mm | |
| - clear space between bottom of the finished floor and walls | 180 mm | |
| - height partition and splash walls | 2040 mm | (infant cubicles 1200 mm) |
| - height front and side walls | 2040 mm | |
| - width and depth of the sanitary cubicle depends on project and/or according to drawing | | |
- Doors**
- self-closing
- Standard dimensions doors** (differences are possible, with the exception of the thickness)
- | | | |
|------------------|---------------|---------------------------|
| - thickness | 13 mm | |
| - height | 2040 mm | (infant cubicles 1200 mm) |
| - width | 615 to 750 mm | (MIVA 915 mm) |
| - entrance width | 600 to 735 mm | (MIVA 900 mm) |
- Hinges and locks**
- Finger safe aluminium translating hinges. Self closing by translation movement, 180 ° degrees opening, including anti-theft device
 - Kupan free and occupied lock with integrated handgrip, natural anodised aluminium, with red-white indication and brass emergency pin, allows opening from the outside in case of an emergency
- Supporting structure**
- reduced quantity of feet, 180 mm high natural anodised aluminium foot with ABS plastic rosette.
- Fittings and Accessories**
- bench and splash wall for showers
 - bench with central locking system for changing cubicles
 - coat hooks, natural anodised aluminium
 - modesty partitions for urinals, 13 mm SGL sheet with aluminium anodised wall clamps
 - soap and shampoo plateaus (planchets)
 - toilet roll holder
 - washstand sheets and washbasins
 - rim/safety locks
 - soap dishes
 - mirrors
 - SGL lockers
 - pictograms
 - lighting galleries
 - aluminium profiles in RAL colour
5. **DRAWINGS**
- By manufacturer made drawings. Also in 3D and BIM
- Working drawing(s) based on supplied principle arrangement drawing(s) by the management
- Amount of supplied copies:
- For approval : PDF format by e-mail
- Definite : PDF format by e-mail
6. **PROCESSING INSTRUCTIONS MANUFACTURER**
- Assembly and mounting**
- pre assembled in factory
- Installation**
- supplied processing regulations in accordance with the manufacturer.
 - if required by KUPAN BV
- Warranty**
- 1 year on hinges and locks
 - 5 years on SGL Sheet/Panels
01. **INDOOR SEPARATION**
- The partition walls in the sanitary spaces as indicated on finished condition and drawings.



ESSENCE LINE



SPECIFICATON DESCRIPTION CUBICLE TYPE "ESSENCE" FLOOR TO CEILING H3000

- 44.42 PRE-ASSEMBLED WALL SYSTEMS
- 44.42.40- a. PANEL SYSTEM WALL, PRE-ASSEMBLED WALL SYSTEMS, SOLID GRADE LAMINATE (SGL)
0. PANEL SYSTEM WALL
1. SANITARY CUBICLE PARTITIONS
- Manufacture : KUPAN B.V. Varsseveld The Netherlands
- Type : Essence Floor to ceiling
- Construction element:**
- Solid Grade Laminate melamine resin sheets (SGL) 13 mm
 - walls are attached internally and upon structural walls by means of natural anodised aluminium continuous U profiles
 - pilasters/end walls are provided with natural anodised aluminium door stop sections with PVC damper for soundproofing
 - places upon aluminium adjustable feet (screwed or glued together on the floor)
 - finish: SGL
- Standard dimensions wall elements** (differences are possible, with the exception of the thickness)
- | | | |
|--|---------|---------------------------|
| - thickness side/partition walls and pilasters (front) | 13 mm | |
| - cubicle height | 3000 mm | |
| - passage height | 2300 mm | |
| - clear space between bottom of the finished floor and walls | - mm | |
| - height partition and splash walls | 2040 mm | (infant cubicles 1200 mm) |
| - height front and side walls | 2040 mm | |
| - width and depth of the sanitary cubicle depends on project and/or according to drawing | | |
- Doors**
- self-closing
- Standard dimensions doors** (differences are possible, with the exception of the thickness)
- | | | |
|-------------------------|---------------|---------------------------|
| - thickness | 13 mm | |
| - height | 2040 mm | (infant cubicles 1200 mm) |
| - width | 615 to 750 mm | (MIVA 915 mm) |
| - entrance width | 600 to 735 mm | (MIVA 900 mm) |
| - door top panels | 13 mm | |
| - door top panel height | 700 mm | |
- Hinges and locks**
- Finger safe aluminium translating hinges. Self closing by translation movement, 180 ° degrees opening, including anti-theft device
 - Kupan free and occupied lock with integrated handgrip, natural anodised aluminium, with red-white indication and brass emergency pin, allows opening from the outside in case of an emergency
- Supporting structure**
- pilasters and partitions mounted within natural anodised U profiles fixed tot the floor with stainless steel screws.
- Fittings and Accessories**
- bench and splash wall for showers
 - bench with central locking system for changing cubicles
 - coat hooks, natural anodised aluminium
 - modesty partitions for urinals, 13 mm SGL sheet with aluminium anodised wall clamps
 - soap and shampoo plateaus (planchets)
 - toilet roll holder
 - washstand sheets and washbasins
 - rim/safety locks
 - soap dishes
 - mirrors
 - SGL lockers
 - pictograms
 - lighting galleries
 - aluminium profiles in RAL colour
5. **DRAWINGS**
- By manufacturer made drawings. Also in 3D and BIM
- Working drawing(s) based on supplied principle arrangement drawing(s) by the management
- Amount of supplied copies:
- For approval : PDF format by e-mail
- Definite : PDF format by e-mail
6. **PROCESSING INSTRUCTIONS MANUFACTURER**
- Assembly and mounting**
- pre assembled in factory
- Installation**
- supplied processing regulations in accordance with the manufacturer.
 - if required by KUPAN BV
- Warranty**
- 1 year on hinges and locks
 - 5 years on SGL Sheet/Panels
01. **INDOOR SEPARATION**
- The partition walls in the sanitary spaces as indicated on finished condition and drawings.



ESSENCE LINE



SPECIFICATON DESCRIPTION CUBICLE TYPE "ESSENCE" FLOOR CONNECTION H2042

- 44.42 PRE-ASSEMBLED WALL SYSTEMS
- 44.42.40- a. PANEL SYSTEM WALL, PRE-ASSEMBLED WALL SYSTEMS, SOLID GRADE LAMINATE (SGL)
0. PANEL SYSTEM WALL
1. SANITARY CUBICLE PARTITIONS
- Manufacture : KUPAN B.V. Varsseveld The Netherlands
Type : Essence floor connection H2042
- Construction element:**
- Solid Grade Laminate melamine resin sheets (SGL) 13 mm
 - walls are attached internally and upon structural walls by means of natural anodised aluminium continuous U profiles
 - pilasters/end walls are provided with natural anodised aluminium door stop sections with PVC damper for soundproofing
 - finish: SGL
- Standard dimensions wall elements** (differences are possible, with the exception of the thickness)
- thickness side/partition walls and pilasters (front) 13 mm
 - cubicle height 2042 mm
 - passage height 1992 mm
 - clear space between bottom of the finished floor and walls - mm
 - height partition and splash walls 2000 mm (infant cubicles 1200 mm)
 - height front and side walls 2000 mm
 - width and depth of the sanitary cubicle depends on project and/or according to drawing
- Doors**
- self-closing
- Standard dimensions doors** (differences are possible, with the exception of the thickness)
- thickness 13 mm
 - height 1960 mm (infant cubicles 1200 mm)
 - width 615 to 750 mm (MIVA 915 mm)
- Hinges and locks**
- Finger safe aluminium translating hinges. Self closing by translation movement, 180 ° degrees opening, including anti-theft device
 - Kupan free and occupied lock with integrated handgrip, natural anodised aluminium, with red-white indication and brass emergency pin, allows opening from the outside in case of an emergency
- Supporting structure**
- floor connection
- Fittings and Accessories**
- bench and splash wall for showers
 - bench with central locking system for changing cubicles
 - coat hooks, natural anodised aluminium
 - modesty partitions for urinals, 13 mm SGL sheet with aluminium anodised wall clamps
 - soap and shampoo plateaus (planchets)
 - toilet roll holder
 - soap dishes
 - pictograms
 - washstand sheets and washbasins
 - mirrors
 - lighting galleries
 - rim/safety locks
 - SGL lockers
 - aluminium profiles in RAL colour
5. **DRAWINGS**
- By manufacturer made drawings. Also in 3D and BIM
Working drawing(s) based on supplied principle arrangement drawing(s) by the management
Amount of supplied copies:
For approval : PDF format by e-mail
Definite : PDF format by e-mail
6. **PROCESSING INSTRUCTIONS MANUFACTURER**
- Assembly and mounting**
- pre assembled in factory
- Installation**
- supplied processing regulations in accordance with the manufacturer.
 - if required by KUPAN BV
- Warranty**
- 1 year on hinges and locks
 - 5 years on SGL Sheet/Panels
01. **INDOOR SEPARATION**
- The partition walls in the sanitary spaces as indicated on finished condition and drawings.



ESSENCE LINE



SPECIFICATON DESCRIPTION CUBICLE TYPE "ESSENCE" FREELY SUSPENDED H2042

- 44.42 PRE-ASSEMBLED WALL SYSTEMS
- 44.42.40- a. PANEL SYSTEM WALL, PRE-ASSEMBLED WALL SYSTEMS, SOLID GRADE LAMINATE (SGL)
0. PANEL SYSTEM WALL
1. SANITARY CUBICLE PARTITIONS
- Manufacture : KUPAN B.V. Varsseveld The Netherlands
Type : Essence freely suspended H2042
- Construction element:**
- Solid Grade Laminate melamine resin sheets (SGL) 13 mm
 - walls are attached internally and upon structural walls by means of natural anodised aluminium continuous U profiles
 - pilasters/end walls are provided with natural anodised aluminium door stop sections with PVC damper for soundproofing
 - finish: SGL
- Standard dimensions wall elements** (differences are possible, with the exception of the thickness)
- thickness side/partition walls and pilasters (front) 13 mm
 - cubicle height 2042 mm
 - passage height 1995 mm
 - clear space between bottom of the finished floor and walls 180 mm
 - height partition and splash walls 1820 mm (infant cubicles 1200 mm)
 - height front and side walls 1820 mm
 - width and depth of the sanitary cubicle depends on project and/or according to drawing
- Doors**
- self-closing
- Standard dimensions doors** (differences are possible, with the exception of the thickness)
- thickness 13 mm
 - height 1820 mm (infant cubicles 1200 mm)
 - width 615 to 750 mm (MIVA 915 mm)
 - entrance width 600 to 735 mm (MIVA 900 mm)
- Hinges and locks**
- Finger safe aluminium translating hinges. Self closing by translation movement, 180 ° degrees opening, including anti-theft device
 - Kupan free and occupied lock with integrated handgrip, natural anodised aluminium, with red-white indication and brass emergency pin, allows opening from the outside in case of an emergency
- Supporting structure**
- headrail in combination with structural walls. If not enough to bear weight, minimal use of feet.
- Fittings and Accessories**
- bench and splash wall for showers
 - bench with central locking system for changing cubicles
 - coat hooks, natural anodised aluminium
 - modesty partitions for urinals, 13 mm SGL sheet with aluminium anodised wall clamps
 - soap and shampoo plateaus (planchets)
 - toilet roll holder
 - washstand sheets and washbasins
 - rim/safety locks
 - soap dishes
 - mirrors
 - SGL lockers
 - pictograms
 - lighting galleries
 - aluminium profiles in RAL colour
5. **DRAWINGS**
- By manufacturer made drawings. Also in 3D and BIM
Working drawing(s) based on supplied principle arrangement drawing(s) by the management
Amount of supplied copies:
For approval : PDF format by e-mail
Definite : PDF format by e-mail
6. **PROCESSING INSTRUCTIONS MANUFACTURER**
- Assembly and mounting**
- pre assembled in factory
- Installation**
- supplied processing regulations in accordance with the manufacturer.
 - if required by KUPAN BV
- Warranty**
- 1 year on hinges and locks
 - 5 years on SGL Sheet/Panels
01. **INDOOR SEPARATION**
- The partition walls in the sanitary spaces as indicated on finished condition and drawings.



ESSENCE LINE



SPECIFICATON DESCRIPTION CUBICLE TYPE "ESSENCE" FREELY SUSPENDED H2262

- 44.42 PRE-ASSEMBLED WALL SYSTEMS
- 44.42.40- a. PANEL SYSTEM WALL, PRE-ASSEMBLED WALL SYSTEMS, SOLID GRADE LAMINATE (SGL)
0. PANEL SYSTEM WALL
1. SANITARY CUBICLE PARTITIONS
- Manufacture : KUPAN B.V. Varsseveld The Netherlands
 Type : Essence freely suspended H2262
- Construction element:**
- Solid Grade Laminate melamine resin sheets (SGL) 13 mm
 - walls are attached internally and upon structural walls by means of natural anodised aluminium continuous U profiles
 - pilasters/end walls are provided with natural anodised aluminium door stop sections with PVC damper for soundproofing
 - finish: SGL
- Standard dimensions wall elements** (differences are possible, with the exception of the thickness)
- | | | |
|--|---------|---------------------------|
| - thickness side/partition walls and pilasters (front) | 13 mm | |
| - cubicle height | 2262 mm | |
| - passage height | 2215 mm | |
| - clear space between bottom of the finished floor and walls | 180 mm | |
| - height partition and splash walls | 2040 mm | (infant cubicles 1200 mm) |
| - height front and side walls | 2040 mm | |
| - width and depth of the sanitary cubicle depends on project and/or according to drawing | | |
- Doors**
- self-closing
- Standard dimensions doors** (differences are possible, with the exception of the thickness)
- | | | |
|------------------|---------------|---------------------------|
| - thickness | 13 mm | |
| - height | 2040 mm | (infant cubicles 1200 mm) |
| - width | 615 to 750 mm | (MIVA 915 mm) |
| - entrance width | 600 to 735 mm | (MIVA 900 mm) |
- Hinges and locks**
- Finger safe aluminium translating hinges. Self closing by translation movement, 180 ° degrees opening, including anti-theft device
 - Kupan free and occupied lock with integrated handgrip, natural anodised aluminium, with red-white indication and brass emergency pin, allows opening from the outside in case of an emergency
- Supporting structure**
- headrail in combination with structural walls. If not enough to bear weight, minimal use of feet.
- Fittings and Accessories**
- bench and splash wall for showers
 - bench with central locking system for changing cubicles
 - coat hooks, natural anodised aluminium
 - modesty partitions for urinals, 13 mm SGL sheet with aluminium anodised wall clamps
 - soap and shampoo plateaus (planchets)
 - toilet roll holder
 - washstand sheets and washbasins
 - rim/safety locks
 - soap dishes
 - mirrors
 - SGL lockers
 - pictograms
 - lighting galleries
 - aluminium profiles in RAL colour
5. **DRAWINGS**
- By manufacturer made drawings. Also in 3D and BIM
 Working drawing(s) based on supplied principle arrangement drawing(s) by the management
 Amount of supplied copies:
 For approval : PDF format by e-mail
 Definite : PDF format by e-mail
6. **PROCESSING INSTRUCTIONS MANUFACTURER**
- Assembly and mounting**
- pre assembled in factory
- Installation**
- supplied processing regulations in accordance with the manufacturer.
 - if required by KUPAN BV
- Warranty**
- 1 year on hinges and locks
 - 5 years on SGL Sheet/Panels
01. **INDOOR SEPARATION**
- The partition walls in the sanitary spaces as indicated on finished condition and drawings.



ESSENCE LINE



SPECIFICATON DESCRIPTION CUBICLE TYPE "ESSENCE" FREELY SUSPENDED WITH BEAM H2150

- 44.42 PRE-ASSEMBLED WALL SYSTEMS
- 44.42.40- a. PANEL SYSTEM WALL, PRE-ASSEMBLED WALL SYSTEMS, SOLID GRADE LAMINATE (SGL)
0. PANEL SYSTEM WALL
1. SANITARY CUBICLE PARTITIONS
- Manufacture : KUPAN B.V. Varsseveld The Netherlands
Type : Essence freely suspended with beam H2150
- Construction element:**
- Solid Grade Laminate melamine resin sheets (SGL) 13 mm
 - walls are attached internally and upon structural walls by means of natural anodised aluminium continuous U profiles
 - pilasters/end walls are provided with natural anodised aluminium door stop sections with PVC damper for soundproofing
 - finish: SGL
- Standard dimensions wall elements** (differences are possible, with the exception of the thickness)
- thickness side/partition walls and pilasters (front) 13 mm
 - cubicle height 2150 mm
 - passage height 2215 mm
 - clear space between bottom of the finished floor and walls 180 mm
 - height partition and splash walls 1820 mm (infant cubicles 1200 mm)
 - height front and side walls 1820 mm
 - width and depth of the sanitary cubicle depends on project and/or according to drawing
- Doors**
- self-closing
- Standard dimensions doors** (differences are possible, with the exception of the thickness)
- thickness 13 mm
 - height 1800 mm (infant cubicles 1200 mm)
 - width 615 to 750 mm (MIVA 915 mm)
 - entrance width 600 to 735 mm (MIVA 900 mm)
- Hinges and locks**
- Finger safe aluminium translating hinges. Self closing by translation movement, 180 ° degrees opening, including anti-theft device
 - Kupan free and occupied lock with integrated handgrip, natural anodised aluminium, with red-white indication and brass emergency pin, allows opening from the outside in case of an emergency
- Supporting structure**
- 150 x 150 mm powder coated aluminium headrail in combination with structural walls. If not enough to bear weight, minimal use of feet
- Fittings and Accessories**
- bench and splash wall for showers
 - bench with central locking system for changing cubicles
 - coat hooks, natural anodised aluminium
 - modesty partitions for urinals, 13 mm SGL sheet with aluminium anodised wall clamps
 - soap and shampoo plateaus (planchets)
 - toilet roll holder
 - washstand sheets and washbasins
 - rim/safety locks
 - soap dishes
 - mirrors
 - SGL lockers
 - pictograms
 - lighting galleries
 - aluminium profiles in RAL colour
5. **DRAWINGS**
- By manufacturer made drawings. Also in 3D and BIM
Working drawing(s) based on supplied principle arrangement drawing(s) by the management
Amount of supplied copies:
For approval : PDF format by e-mail
Definite : PDF format by e-mail
6. **PROCESSING INSTRUCTIONS MANUFACTURER**
- Assembly and mounting**
- pre assembled in factory
- Installation**
- supplied processing regulations in accordance with the manufacturer.
 - if required by KUPAN BV
- Warranty**
- 1 year on hinges and locks
 - 5 years on SGL Sheet/Panels
01. **INDOOR SEPARATION**
- The partition walls in the sanitary spaces as indicated on finished condition and drawings.



SPECIFICATION DESCRIPTION CUBICLE TYPE "ESSENCE" FREELY SUSPENDED WITH BEAM H2370

- 44.42 PRE-ASSEMBLED WALL SYSTEMS
- 44.42.40- a. PANEL SYSTEM WALL, PRE-ASSEMBLED WALL SYSTEMS, SOLID GRADE LAMINATE (SGL)
0. PANEL SYSTEM WALL
1. SANITARY CUBICLE PARTITIONS
- Manufacture : KUPAN B.V. Varsseveld The Netherlands
Type : Essence freely suspended with beam H2370
- Construction element:**
- Solid Grade Laminate melamine resin sheets (SGL) 13 mm
 - walls are attached internally and upon structural walls by means of natural anodised aluminium continuous U profiles
 - pilasters/end walls are provided with natural anodised aluminium door stop sections with PVC damper for soundproofing
 - finish: SGL
- Standard dimensions wall elements** (differences are possible, with the exception of the thickness)
- | | | |
|--|---------|---------------------------|
| - thickness side/partition walls and pilasters (front) | 13 mm | |
| - cubicle height | 2370 mm | |
| - passage height | 2220 mm | |
| - clear space between bottom of the finished floor and walls | 180 mm | |
| - height partition and splash walls | 2040 mm | (infant cubicles 1200 mm) |
| - height front and side walls | 2040 mm | |
| - width and depth of the sanitary cubicle depends on project and/or according to drawing | | |
- Doors**
- self-closing
- Standard dimensions doors** (differences are possible, with the exception of the thickness)
- | | | |
|------------------|---------------|---------------------------|
| - thickness | 13 mm | |
| - height | 2020 mm | (infant cubicles 1200 mm) |
| - width | 615 to 750 mm | (MIVA 915 mm) |
| - entrance width | 600 to 735 mm | (MIVA 900 mm) |
- Hinges and locks**
- Finger safe aluminium translating hinges. Self closing by translation movement, 180 ° degrees opening, including anti-theft device
 - Kupan free and occupied lock with integrated handgrip, natural anodised aluminium, with red-white indication and brass emergency pin, allows opening from the outside in case of an emergency
- Supporting structure**
- 150 x 150 mm powder coated aluminium headrail in combination with structural walls. If not enough to bear weight, minimal use of feet
- Fittings and Accessories**
- bench and splash wall for showers
 - bench with central locking system for changing cubicles
 - coat hooks, natural anodised aluminium
 - modesty partitions for urinals, 13 mm SGL sheet with aluminium anodised wall clamps
 - soap and shampoo plateaus (planchets)
 - toilet roll holder
 - washstand sheets and washbasins
 - rim/safety locks
 - soap dishes
 - mirrors
 - SGL lockers
 - pictograms
 - lighting galleries
 - aluminium profiles in RAL colour
5. **DRAWINGS**
- By manufacturer made drawings. Also in 3D and BIM
Working drawing(s) based on supplied principle arrangement drawing(s) by the management
Amount of supplied copies:
For approval : PDF format by e-mail
Definite : PDF format by e-mail
6. **PROCESSING INSTRUCTIONS MANUFACTURER**
- Assembly and mounting**
- pre assembled in factory
- Installation**
- supplied processing regulations in accordance with the manufacturer.
 - if required by KUPAN BV
- Warranty**
- 1 year on hinges and locks
 - 5 years on SGL Sheet/Panels
01. **INDOOR SEPARATION**
- The partition walls in the sanitary spaces as indicated on finished condition and drawings.